


Construction

1 Conductor Diameter	Solid Bare Copper AWG 23
2 Insulation Color Code Pair 1 Pair 2 Pair 3 Pair 4	Solid PE Blue/White-Blue Orange/White-Orange Green/White-Green Brown/White-Brown
3 Central Cross	PE Spline
4 Synthetic Polyester Foil Coverage	>100%
5 Drain Wire Diameter (mm)	Solid Tinned Copper 0.40±0.05
6 Shielding Coverage	Al / PES >100%
7 Sheath Diameter (mm) Color	LSZH 7.20±0.40 Blue en color on request

Marking

BCABLES SMART  LINE EN 50575 C_{ca} S1D1A1 DOP-BSY32B-XX ZZWWYY 4 PAIRS AWG 23 F/UTP CAT 6A 500 MHZ - 100 OHM - DELTA - ISO 11801 TIA/EIA 568-B2 CE LSZH F2 SA SD 001M

Standards

ISO/IEC 11801-1:2017 (Ed. 1.0) / ISO/IEC 11801-2:2017 (Ed. 1.0)
IEC 61156-5:2012 (Ed. 2.1)
EN 50173-1:2011 / EN 50173-2:2007 including amendment A1:2010
EN 50288-11-1:2012 - ANSI/TIA-568-C.2:2009
Euroclass C_{ca} s1d1a1

Electrical Characteristics

Characteristics Impedance (Ω) from 1 to 100 MHz	100 ± 15
from 100 to 250 MHz	100 ± 25
Conductor DC Resistance @ 20°C (Ω/km)	95
Nominal Velocity of Propagation	75%

Frequency (MHz)	Attenuation (dB/100m)	Return Loss (dB)	NEXT (dB)
4	3.8	23.0	65.0
10	5.9	25.0	59.0
16	7.5	25.0	56.0
20	8.4	25.0	55.0
31.25	10.6	23.6	52.0
100	19.8	20.1	44.0
200	29.0	18.0	40.0
250	32.8	17.3	38.3
300	36.4	16.8	37.1
500	48.9	15.2	33.8

