


**Construction**

<b>1 Conductor</b>	<b>Solid Bare Copper</b>
Diameter	AWG 23
<b>2 Insulation Color Code</b>	<b>Solid PE</b>
Diameter (mm)	0.85 ± 0.05
Pair 1	Blue/White-Blue
Pair 2	Orange/White-Orange
Pair 3	Green/White-Green
Pair 4	Brown/White-Brown
<b>3 Al-Pet Foil</b> (on each pair, Al outside)	
Coverage	≥115%
<b>4 Drain Wire</b>	
<b>5 Outer Sheath</b>	<b>LSZH</b>
Thickness (mm)	0.5
Diameter (mm)	7.60 ±0.30
Color	Green - RAL 6018
	Color on request

**Marking**

B-CABLES SMART  LINE EN50575 Cca s1d1a1 DOP-BSYXXX-4 PAIRS AWG23 U/FTP CAT 6A 500MHZ – 100 OHM – DELTA – ISO11801/ TIA-EIA 568-B.2 CE LSZH F2 SA SD 001M

**Standards**

ISO/IEC 11801-1:2017 (Ed. 1.0) / ISO/IEC 11801-2:2017 (Ed. 1.0)  
IEC 61156-5:2012 (Ed. 2.1)  
EN 50173-1:2011 / EN 50173-2:2007 including amendment A1:2010  
EN 50288-11-1:2012 - ANSI/TIA-568-C.2:2009  
IEEE 802.3 A-NEXT ISO/IEC TR 24750 A-FEXT

The alien NEXT or alien FEXT coupled into a link segment is specified as the power sum of the individual alien NEXT or alien FEXT disturbers.  
The link segment shall meet the values determined using Equation (xx) dB

ANEXT(f) ≥ 37.5-17\*log(f/MHz/20) (dB)  
AFEXT(f) ≥ 38-18\*log(f/MHz/20) (dB)

**Euroclass Cca s1d1a1**

**Electrical Characteristics**

Characteristics Impedance (Ω)	
@ 1~250 MHz (Ω)	100 ± 15
@ 250~500MHz (Ω)	100 ± 25
Conductor DC Resistance @ 20°C (Ω/km)	95
Nominal Velocity of Propagation	75%

	Attenuation	Return Loss	NEXT
4 MHz	3.8	23.00	66.3
10 MHz	5.9	25.00	60.3
16 MHz	7.5	25.00	57.2
25 MHz	9.4	25.00	54.3
31.25 MHz	10.5	23.6	52.9
100 MHz	19.1	20.1	45.3
200 MHz	27.6	18.0	40.8
250 MHz	31.1	17.3	39.3
300 MHz	34.3	17.3	38.1
400 MHz	40.1	17.3	36.3
500 MHz	45.3	17.3	34.8

